

# FM75 EVO

# TROLLEY MANUAL HEAT-SHRINK - FULL OPTIONAL - SEALING BAR 420X280 MM



## **DESCRIPTION**

**Minipack®-Torre** has never renounced the pioneering spirit that has always accompanied it. It was precisely the invention of the first **chamber machine**, in fact, to decree the birth of the company over 40 years ago, with the first patent in 1976. But ideas cannot be stopped. Today, Minipack®-torre launches a new series that is the result of years of research and development and summarises all the qualities of its compact **packaging machines**: reliable, easy to use, durable.

#### **TECHNICAL FEATURES**


Electrical power supply V 200/230



Phase	ph	1
Maximum power installed	kW	3,35 (200V) 3,45 (230V)
Hourly output	pcs/h	0-300
Available dimensions of the sealing bars	mm	420x280
MAX product size	mm	400x250x160
MAX Reel Dimensions (diameter)	mm	250
MAX Reel Strip Dimensions (width)	mm	500
Work Surface Height	mm	940
Machine dimensions with the lid open	mm	1160x700x1310
Machine dimensions with the lid closed	mm	1160x700x1150
Weight (Net/Gross)	Kg	112/136

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

### **TECHNICAL DRAWING**



### **TECHNICAL SOLUTIONS**

- High-performance steel resistors: shrinking time cut by 50% and heating time cut by 60%
- Soft Shrink fan speed adjustment: perfect heat-shrinking also on very light or flexible products. Sealed areas do not open. Extremely quiet. Exclusive patent
- Comfort Zone Fan Stop: the fan stop is a "green" solution that allows to save 20% more energy and
  provides greater operator comfort during packaging, since the fan stops when the chamber opens



- o New latest-generation board: quality components. 4-digit display
- Waste rewinder: productivity up by 20%
- $\circ~$  Sealing bar cooling: increased productivity and improved sealing.